

# XTRAVAC TS340

Vacuum Packaging Machines



## Machine Information XTRAVAC TS340

Seal only	Yes
Vacuum / Gas	Yes
Skin	No
Max. Tray Dimension 1-up	340 x 250 x 110 mm
Max. Tray Dimension 2-up	146 x 250 x 110 mm
Max. Tray Dimension 3-up	88 x 250 x 110 mm
Max. Tray Dimension 4-up	146 x 111 x 110 mm
Max. Tray Dimension 6-up	88 x 111 x 110 mm
Min. Tray Dimension round	90 mm
Min. Tray height	15 mm
Max Tray height	110 mm
Easy-peel corner	Optional
Shrink film	Optional
Max roll diameter	340 mm
Max Film width	400 mm
Film core mm	75
Vacuum pump size [m3/hp]	40/2.5
Water Cooling	No
Printed Film	Yes
Automatic Die movement	Yes
Cycles per minute Seal only	4-5
Cycles per minute Seal & Gas	2-3
Machine on casters	Yes
Gas pressure [bar]	6
Compressed air [bar]	6
Compressed air	80 psi at 1 cfm
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Machine weight kg	225
Machine weight lbs	490
Gross weight kg	272
Gross weight lbs	590
Package Dimension inch	40" x 31" x 64"
Package Dimension mm	1000 x 790 x 1620 mm
USA	
# 3 Plastic tray dim.	172 mm x 222 mm 1 up
# 5 - SEL Universal tray dim.	207 mm x 262 mm 1 up
# 9 - LEL Family tray dim.	260 mm x 314 mm 1 up
# 10 - LEL Plastic tray dim.	172 mm x 273 mm 1 up
Europe	
187x137mm SEL	2 up
190x144mm SEL	2 up
227x178mm LEL	1 up
230x145mm (XPS tray) SEL	2 up
265x160mm (1/4 Gastronorm) LEL	1 up
SEL Short Edge Leading	
LEL Long Edge Leading	

## Model TS340

Large, preformed tray packaging machine features sanitary design and stainless steel construction. Automatic chamber movement design to accommodate high production volume. User-friendly digital controls with storable process control program. Interchangeable tooling for maximum flexibility. Automatic trim wind up. High quality Busch pump standard. Features locking casters.

**XTRAVAC**  
 Vacuum Packaging Machines  
 VC999 Packaging Systems, Kansas City MO  
 Tel. 800-728-2999, Fax 816-472-1999